



**VOLVO** 265





You sit on real leather in the 265 GL. There's plenty of room for five as well as 42 cu.ft. of luggage.



The instrumentation includes a comprehensive system of warning and reminder lights.

	265 DL	265 GL
<b>Engine</b>		
Designation . . . . .	B27A	B27A
Configuration . . . . .	V6	V6
Displacement cm <sup>3</sup> . . . . .	2664	2664
Bore x stroke, mm . . . . .	88.0 x 73.0	88.0 x 73.0
Max output hp at r/m DIN . . . . .	125/5250	125/5250
Max output kW at r/s DIN . . . . .	92/88	92/88
Max torque kpm r/m DIN . . . . .	20.0/3500	20.0/3500
Max torque Nm at r/s DIN . . . . .	196/58	196/58
Compression ratio. . . . .	8.7:1	8.7:1
<b>Equipment<sup>1)</sup></b>		
Headlight washers/wipers . . . . .	—	Yes
Instruments . . . . .	Clock	Clock, Tachometer
Steering wheel diameter/type . . . . .	400 mm	400 mm/integral foam clad
Tinted glazing . . . . .	—	Yes
Vanity mirror . . . . .	—	In glovebox
Upholstery . . . . .	Cloth	Leather
Electrically heated driving seat . . . . .	—	Yes
Oddments storage. . . . .	In front doors	In front doors and on front seat backrests

<sup>1)</sup> The equipment listed in the above table is additional to the standard equipment specified in the following.

#### Engine

Water-cooled, V6 engine with single cross-draught carburettor. Engine block and cylinder heads of aluminium alloy. Overhead camshafts. Contactless, transistorised ignition system. Economy grade petrol.

#### Cooling system

Sealed and frost-proofed. Volume 2.4 Imp. galls./10.9 litres.

#### Electrical system

12V/70Ah battery. 55A alternator.

#### Fuel tank

Safety location beside rear axle, below rear underbody. Capacity approx. 13.2 Imp. galls./60 litres.

#### Transmission

Diaphragm spring clutch. Fully synchronised, four-speed, manual gearbox with overdrive operating

on 4th gear. Automatic transmission is optional on the 265 DL and standard on the Volvo 265 GL.

#### Steering gear

Rack and pinion. Safety steering column, two-part, telescopic. Steering ratio 17.1:1. Power assisted. 3.5 turns from lock to lock.

#### Suspension

Front: spring strut type with stabiliser. Rear: live, carried in rubber-mounted control arms and torque rods, transverse location by track rod.

#### Wheels and tyres

Steel braced, radial ply tyres, dimension 185 SR 14 on 5.5 J-14" rims.

#### Braking system

Power assisted, all-disc, dual circuit, triangle-split system. Each circuit operates simultaneously on both front wheels and one each of the rear wheels. Relief valves prevent premature rear wheel lock-up in emergency situations. Master cylinder of stepped-bore type. Rust-resistant brake pipes of copper and nickel alloy throughout. Handbrake operates on separate rear wheel drums.

#### Instrumentation

Padded safety fascia. Rheostat-controlled instrument lighting, selected controls have concealed lighting. Six-figure mileometer with tripmeter. Fuel gauge. Coolant temperature gauge. Warning lamps for: charging, oil pressure, turn indicators, main beam, handbrake application, brake circuit failure and bulb integrity sensor. Illuminated glovebox. Combined steering and ignition lock. Quartz clock. Centre console: switches for electrically heated rear window and four-way hazard warning lights. Also; controls for heating and ventilation system, "fasten seat belts" reminder, cigar lighter and ashtray. Radio compartment.

#### Other standard equipment

Combined stalk for turn indicators, main and dipped beam with head-

light flasher. Combined stalk for two-speed windscreen wipers and electric windscreen washers. Rectangular halogen headlights with separate reflectors for main and dipped beams. Automatic day running lights. Automatic reversing lights. Four inertia reel seat belts with static lap belt for centre rear passenger. Rear "fasten seat belts" reminder. High impact type laminated windscreen. Front head-restraints. Driving seat height adjustment by levers. Adjustable lumbar support. Child-proof locks in both rear side doors and tailgate. Impact absorbing bumpers. Door mirror on driver's side. Moulded glassfibre roof lining. Engine compartment lighting and courtesy light beside tailgate. Electrically heated tailgate window also has wiper and washer. Mud-flaps all round. Towing points front and rear.

#### Exterior dimensions

(in/mm)  
Overall length . . . . . 193/4898  
Overall width . . . . . 67.2/1707  
Track:  
Front . . . . . 56.3/1430  
Rear . . . . . 53.5/1360  
Turning circle  
between kerbs . . . . . 32 ft. 2 in/9.8 m

#### Cargo area dimensions

Volume, rear seat:  
in use approx . . . . . 42 cu.ft./1.2 m<sup>3</sup>  
folded approx . . . . . 67 cu.ft./1.9 m<sup>3</sup>  
Volume, concealed cavity  
approx. . . . . 2.3 cu.ft./65 dm<sup>3</sup>  
Tailgate opening max.  
width . . . . . 457 in/1160 mm


#### Weights

(lb/kg)  
Kerb weight approx. . . . . 3164/1435  
Gross weight approx. . . . . 4299/1950  
Trailer weight . . . . . 3307/1500

#### Warranty

Twelve-month warranty including parts and labour irrespective of mileage.

The factory reserves the right to make changes at any time, without notice, to prices, colours, materials, equipment, specifications and models and also to discontinue models.



# VOLVO

RSP/PV 4225-77. Engelska/England