Service Manual

Fault tracing

Section 2	Group 23
LH-Jetro system B21F	onic



Contents

System description		1
System components and specifications		3
Special tools (instruments)		10
Fault tracing electric circuits – Preparations for testing	Operations 1–7	11
- Circuit activated by ignition switch	A1-A3	13
- Circuit energized when starter motor is operating	B1-B3	14
- Power supply from system relay	C1-C3	15
- Circuit to fuel pumps	D1-D5	16
- Grounded terminals	E1-E3	18
- Injector circuits	F1-F3	19
- Coolant temperature sensor circuit	G1-G3	20
- Vacuum switch curcuit	H1-H3	21
- Air mass meter circuit	11-14	22
Wiring diagram		24

TP 30413/1 6000.04.82 Printed in U.S.A.

System description



133502

LH-Jetronic is a newly designed fuel injection system. It utilizes a combination of all the best features known today.

It operates with a moderate fuel pressure which is held constant by a line pressure regulator. Injection is by means of electrically controlled solenoid valves in the **injectors** which squirt fuel close to the engine intake valves. The injection duration can be measured in milliseconds and is controlled by an **electronic control unit**. The electronic control unit receives signals on various driving, engine and ambient conditions from a set of **sensors.** Most important is the **air mass meter**. It utilizes a system that continuously measures the **mass**

Location of components.

of air entering the induction system. This is accomplished by a platinum wire filament which is located in the intake air stream. It is held at a certain temperature above intake air temperature by a system of amplifiers, resistors and comparators. The current needed to do this is measured and a corresponding signal sent to the electronic control unit. When the engine stops, dirt build-up on the platinum wire filament is burned off by electrically raising the filament temperature to 1050° = 1920°F for less than one second. If dirt was allowed to stay on the filament, false signals would be received and the electronic control unit would order incorrect air/fuel mixture.



133503

The LH-Jetronic system consists of three functional sections:

Electronic Control Unit.

Receives and evaluates readings from the sensors around the engine. It includes a microprocessor and calculates the correct amount of fuel to be injected. It evaluates variations in engine conditions and produces a control signal to the injectors.

Fuel system.

Carries fuel from the tank through a fuel feed pump in the tank, an in-line fuel pump and a fuel filter to the injection manifold.

The line pressure regulator supplies injectors with fuel which is regulated to a constant pressure in relation to the pressure in the intake manifold.

A cold start injector supplies extra fuel to the engine

when starting cold. The electrical supply to this injector is controlled by the thermal time switch.

Sensors.

Measure the most important combustion parameters and transmit signals to the Electronic Control Unit.

- Air mass meter measures the induction air mass.
- Vacuum switch, indicates part load and full load/idle conditions.
- Engine speed is monitored by a connection to the ignition coil.
- Oxygen sensor (Lambda-sond) checks exhaust gas contents.
- Coolant temperature sensor checks engine coolant temperature.
- During starting a signal is sent from the ignition switch to the Electronic Control Unit to obtain a start program.

Group 23 Fuel system

System components and specifications



Fuel feed pump (tank pump).

Electrically operated vane pump, completely immersed in the gasoline in the fuel tank. It feeds fuel to the (main) fuel pump via a mesh screen and a check valve.

133175



Fuel pump and fuel filter are attached to a bracket underneath the car, under left rear seat.

Fuel pump.

Electrically operated roller pump. Equipped with check valve and overpressure relief valve, which opens in case the system (particularly the fuel filter) becomes clogged and fuel pressure rises too high.

Fuel filter.

Has a paper element with a very small pore size and a mesh to trap any particles that may fall away from the paper element. The complete filter unit is discarded when replaced.



Injectors.

Located on the intake manifold and connected by the injection manifold, which has connectors for the line pressure regulator and the cold start injector.

The injectors are solenoid-operated valves. The electronic Control Unit controls the duration of the injection time.





Line pressure regulator.

Maintains a fuel pressure of 43.5 psi (early production vehicles: 35 psi) above intake manifold pressure. Excess fuel is bled off to the fuel tank via a return line.

psi	Volvo P/N	Bosch No.
35	1306935	0 280 160 214
43.5	1306965	0 280 160 213

133179



Cold start injector.

Supplies extra fuel to the engine and is controlled by the thermal time switch. The cold start injector is a solenoidoperated valve and operates when the starter is energized.

133180



Thermal time switch.

Controls current to the cold start injector and is influenced by engine coolant temperature. It causes termination of cold start fuel injection at engine temperatures above $35^{\circ}C = 95^{\circ}F$ (early production vehicles: $15^{\circ}C = 60^{\circ}F$). A heating coil, acting on a bimetal strip, provides for maximum injection time at low temperatures. Injection time decreases at higher temperatures.

The thermal time switch and cold start injector only operate while the starter motor is switched on.



Vacuum switch.

"Used to indicate full load/idle (low ported vacuum) and part load conditions (maximum vacuum)."

133182



Engine speed and injection timing.

Engine speed pulses are tapped from the low tension side of the ignition coil. Provide both engine speed and injection timing information to the Electronic Control Unit.





Coolant temperature sensor.

Is screwed into the cylinder head. As the engine coolant temperature increases, the resistance in the sensor falls, giving an analog temperature signal to the Electronic Control Unit.

Graph at left shows how coolant temperature sensor resistance changes with temperature.

Below are three test point values, taken from diagram:

- $-10^{\circ}C = 14^{\circ}F$ $20^{\circ}C = 68^{\circ}F$ $80^{\circ}C = 175^{\circ}F$
- 7000–116000 ohms 2100–2900 ohms 270–390 ohms

Oxygen sensor (Lambda-sond).

Is located in the exhaust manifold. It measures the oxygen level in the exhaust gases and provides an electrical signal to the Electronic Control Unit.







133190





Fuel pump relay.

Energizes the fuel feed pump (tank pump) via a separate fuse, and the main fuel pump.

System relay.

Provides current to the Electronic Control Unit. It is energized during filament dirt burn-off after the ignition has been switched off.

Air mass meter.

Is unique to the LH-Jetronic system. It measures air flow by mass (CI fuel injection system measures by volume). The basic sensing information is provided by a heated platinum wire.

When engine is stopped, dirt build-up on the platinum wire filament is burned off electrically by raising the filament temperature to 1050°C for less than one second.

Group 23 Fuel system



CO adjustment is accomplished by a screw on the air mass meter. The screw is connected by a spring to a linear potentiometer of 1000 ohms. The potentiometer is located on the circuit board inside the air mass meter. It has a range of 15 turns and lacks distinct end stops. The potentiometer adds a voltage to the output signal from the air mass meter. The amount of fuel injected can be changed by 40%. Zero ohms on the potentiometer, measured across terminals 6 and 12, provides maximum lean condition. Turning the screw counter-clockwise makes the idle mixture richer.

Idle CO should be 0.6% (0.4–0.8% permitted) with the oxygen sensor disconnected.

When delivered from factory, the CO adjustment screw is sealed by an aluminium plug with a hardened steel insert.

133501





Electronic Control Unit (ECU).

It is the brain of the system. It receives and evaluates readings from the various sensors. It includes a microprocessor which calculates the correct amount of fuel to be injected. The micro-processor is programmed to take account of all possible variations in engine conditions and to produce a control signal to the injectors.

Group 23 Fuel system



Removing connector on Electronic Control Unit.

Press lock tab UP, then FOLD out connector upper part. DO NOT pull straight out.



133149

Terminal

number

- 1 Input, engine speed from terminal 1 on ignition coil.
- 3 Input, from vacuum switch.
- 4 Input, from terminal 50 on starter motor.
- 5 Ground, for electronics in Electronic Control Unit.
- 6 Ground, for electronics in air mass meter.
- 7 Input, from air mass meter.
- 8 Control signal, filament burn-off.
- 9 Output, current to air mass meter.
- 10 Input, current from system relay.
- 11 Injector test.
- 12 Input, CO setting.
- 13 Input, from coolant temperature sensor.
- 14 Output, control current to injectors 3+4.

Terminal

number

- 15 Output, control current to injectors 1+2.
- 16 Ground, for electronics in Electronic Control Unit.
- 17 Ground, for electronics in Electronic Control Unit.
- 19 Shield for wire to terminal 1 on ignition coil.
- 20 Input, ignition ON, from terminal 15 on ignition coil, or terminal 1 on AC relay.
- 22 Output, to LH-Jetronic system testing pick-up point.
- 23 Shield for wire to oxygen sensor.
- 24 Input, from oxygen sensor.
- 28 Output, control ground for fuel pump relay.
- 34 Output, control ground for system relay.

Instruments to use -



Voltmeter.

Only battery (system) voltage is being measured. Any ordinary instrument with a measuring range of approx. 0-15 V (0-20 V) can be used.

133426



Ohmmeter.

Must be a good instrument, capable of accurately measuring 8–16 ohms and 200–1,200 ohms.





Test lamp.

System voltage and currents are low. Therefore many faults are caused by bad connections in multipin connectors.

In some tests, it is suggested an alternate testing method: using a test lamp. It uses more current than a voltmeter and might in some cases reveal a bad connection better.

Fault tracing electric circuits

A simple, but very efficient, way to fault trace the LH-Jetronic system is to check all the electric circuits ending at the connector of the Electronic Control Unit. The tests will thus indicate condition of all components and wires leading to the tested terminal.

If there is a problem, yet all tests prove positive, this indicates a fault in the Electronic Control Unit. There are no procedures included on how to test it. Install a correct Electronic Control Unit to see that the problem disappears.

Important!

First test all circuits according to the fault tracing procedures outlined in this manual. If the Electronic Control Unit is replaced first, a faulty circuit may destroy the new Electronic Control Unit the same way as the original one.





Testing circuit activated by ignition switch -

A1





133411



133394



Test voltage across terminal 20 in connector and ground. Ignition ON.

.

Alt. Also a test lamp can be used for this test.

A3

A2

System (battery) voltage.

Alt. Test light illuminates fully.

If not, check:

 Wiring, following wiring harness backward to ignition switch.

В Testing circuit energized when **B1** starter motor is operating green-blue ignition switch blue start inhibitor switch +12V (auto trans.) rea connector **Electronic Control Unit** ello blue-30 50





System (battery) voltage.

Alt. Test light illuminates fully.

If not, check: Wiring and connector, following wiring harness backward to ignition switch.



• Testing circuit to fuel pumps

D1





Electronic Control Unit connector.







E Testing grounded terminals ·



Using ohmmeter.

Connect one ohmmeter test point to ground.

Connect other test point to, in turn:

- Terminal 5.
- Terminal 16.
- Terminal 17.

Resistance should be zero (zero reading on ohmmeter).

E1

E2



Alt.

Using test lamp.

Connect test lamp lead to battery positive terminal (any place with full battery voltage).

Connect test lamp test point to, in turn:

- Terminal 5.
- Terminal 16.
- Terminal 17.

Test light should illuminate fully at each one of this terminals.

133399





G1







H1





133506



Connect vacuum pump and vacuum gauge to vacuum switch.

НЗ

H2



Check resistance.

Connect ohmmeter across terminals 3 and 5.

- With no vacuum pumped resistance should be zero.
- Pump vacuum to 4 in. Hg. Resistance very high (infinite).

Incorrect readings:

- Very high resistance with no vacuum pumped indicates open circuit.
- Zero resistance when vacuum is pumped indicates shorted circuit.



Testing circuits

14



Air mass meter with seal removed.

Turn CO adjustment screw on air mass meter. Resistance should vary from 0 ohms at full clockwise position to 1000 ohms at full counterclockwise position.

Incorrect readings:

- Slightly incorrect readings indicate incorrectly adjusted air mass meter.
- Zero resistance at full counterclockwise position indicates shorted circuit.
- Very high resistance at full clockwise position indicates open circuit.

Group 23 Fuel system

LH-Jetronic fuel injection system



- A Fuel tank pump
- **B** Vacuum switch
- C Tachometer
- D Fuse box
- E Capacitor, tank pump
- F Connector, tank pump
- G System relay
- H Starter motor
- I Ignition coil
- J Test pick-up connectors
- K Air mass meter
- L Temperature sensor
- M Thermal time switch
- N Injectors (four)
- O Oxygen sensor
- P Cold start injector
- R Connector, Electronic Control Unit (ECU)
- S Fuel pump (main pump)
- T Fuel pump relay



Fuse No. 5: Fuel feed pump (tank pump)

Fuse No. 7: Fuel pump (main pump)

Fuse No. 13: Instruments Turn signals Seat belt warning System relay



ill. 133445 M

Group 23 Fuel system LH-Jetronic wiring diagram



Starting engine cold.

The thermal time switch (M) reduces cold start injector (P) operating time as coolant temperature rises. Injection terminates completely at $15^{\circ}C = 59^{\circ}F$.

Vacuum switch (B) normally grounds terminal 3 of the ECU.

Legend:

- A Fuel tank pump
- **B** Vacuum switch
- C Tachometer
- D fuse box
- E Capacitor, tank pump
- F Connector, tank pump
- G System relay
- H Starter motor
- I Ignition coil
- J Test pick-up connectors K Air mass meter
- K Air mass meter L Temperature sensor
- M Thermal time switch
- N Injectors (four)
- O Oxygen sensor
- P Cold start injector
- R Connector, Electronic Control Unit
- S Fuel pump (main pump)
- T Fuel pump relay

Starting engine warm.

Vacuum switch (B) normally grounds terminal 3 of the ECU.

The ECU receives input signals from the various sensors. Soon after start, the oxygen sensor (O) is heated up by the exhaust gases and starts to signal the ECU.

Group 23 Fuel system LH-Jetronic wiring diagram



Engine running.

Various signals are received and processed by the Electronic Control Unit:

The air mass meter (K) measures the inducted air mass.

The temperature sensor (L) senses coolant temperature.

Terminal 1 receives an **engine speed** signal from the ignition coil.

The oxygen sensor (O) checks the exhaust gas contents.

Common conditions.

As soon as the **ignition** is switched ON, voltage is also fed to terminal 20 of the ECU (Electronic Control Unit). This voltage energizes the various circuits of the ECU.

When the ignition switch energizes the **starter** motor, a signal is also sent to terminal 4 of the ECU.

Signals that the engine is **rotating** are fed from the ignition switch to terminal 1 of the ECU. These signals will cause energizing of system relay (G) and fuel pump relay (T) and thereby also energize terminal 10 of the ECU.

The air mass meter (K) measures the **inducted air mass** and provides an input signal to terminal 7 of the ECU.

Under all conditions, the temperature sensor (L) senses **coolant temperature** and sends corresponding signal to the ECU terminal 13.

Engine stalled.

Ignition ON but engine not running. Engine at normal operating temperature. There are no speed signals from the ignition coil, so the control ground circuit for the fuel pump relay (T) and system relay (G) is opened. The system becomes inactive and the fuel pumps stop.